

# ARCHIE

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 18 W > 990 Lm
- 24 W > 1320 Lm
- 36 W > 1980 Lm



## General information

---

- Mounting type: Applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -20 / +40
- UGR: <19
- CRI: >80
- PF: >0.95
- Angle: 10/15/30

## Applications

---

- Architectural lighting

## Description

---

- Archie is an outdoor LED floodlight that can be used for simplified architectural lighting of buildings.
- It is made of high quality materials, finished to meet even the highest customer demands.

## Benefits

---

- Aluminium alloy body, cast and finished, electrostatically painted, black
- Transparent, tempered, PC disperser.

## Body & Optics

---

- Aluminium alloy body, cast and finished, electrostatically painted, black.
- Transparent, tempered, PC disperser.



**IP65 IK08**

# ARCHIE

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
ARCH118WW-BK	18	990	55	3000K	Φ350x52x39	0.95
ARCH124WW-BK	24	1320	55	3000K	Φ510x52x39	1.5
ARCH136WW-BK	36	1980	55	3000K	Φ1000x52x39	2.8

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	NA	NA	NA