

ATHENA



Power^[W] / Luminosity^[Lm]

- 8 W > 600 Lm
- 15 W > 1125 Lm
- 18 W > 1350 Lm
- 27 W > 2025 Lm



General information

- Mounting type: Suspended
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +50
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 90

Applications

- Commercial, Residential, Office, Horeca, Medical lighting

Description

- The Athena lighting system can replace traditional fixtures perfectly.
- Thanks to the light guide diffuser, the lamp has a uniform and efficient light beam, low glare, low dazzle factor and excellent eye protection.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

Body & Optics

- Body in pure aluminium, cast and finished, electrostatically painted.
- PMMA disperser, matte milky-white

ATHENA

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
ATH08W-WH/BK/S/G	8	600	75	6000K	Φ180x50	2.4
ATH08NW-WH/BK/S/G	8	600	75	4000K	Φ180x50	2.4
ATH08WW-WH/BK/S/G	8	600	75	3000K	Φ180x50	2.4
ATH15W-WH/BK/S/G	15	1125	75	6000K	Φ450x50	3.8
ATH15NW-WH/BK/S/G	15	1125	75	4000K	Φ450x50	3.8
ATH15WW-WH/BK/S/G	15	1125	75	3000K	Φ450x50	3.8
ATH18W-WH/BK/S/G	18	1350	75	6000K	Φ550x50	5.2
ATH18NW-WH/BK/S/G	18	1350	75	4000K	Φ550x50	5.2
ATH18WW-WH/BK/S/G	18	1350	75	3000K	Φ550x50	5.2
ATH27W-WH/BK/S/G	27	2025	75	6000K	Φ850x50	6.2
ATH27NW-WH/BK/S/G	27	2025	75	4000K	Φ850x50	6.2
ATH27WW-WH/BK/S/G	27	2025	75	3000K	Φ850x50	6.2

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	Yes	NA	NA	External	External	External	External