

Aurora

40W 3400 Lm / 3450 Lm / 3500 Lm



Scope of application

Commercial / Office / Conference Halls and Classrooms / Medical / Advertising

Description

Aurora is a luminaire with COB LED technology.

Simple and sleek look.

Lighting device made of unit cast aluminium alloy, with a good thermal dissipation effect.

High-temperature resistant, transparent glass.

Advantages

High luminous efficiency and energy saving.

Fitting

Fitting made of cast and finished aluminium alloy, frosted white or black powder coated.

Optics

PMMA, PC or glass transparent lens.

General Information

Mounting type: Suspended, Surface-mounted

LED type: COB

Voltage: 220-240 VAC / 50-60 Hz

Operating temperature: -10 / +45

UGR: <19

CRI: >80

PF: >0.95

Angle: 24.50


Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm / W]	Colour Temp. ^[K]	Dimensions ^[mm]	Weight ^[kg]
AU40WW-MW/BK	40	3400	85	3000	φ58x175	1.2
AU40NW-MW/BK	40	3450	86	4000	φ58x175	1.2
AU40W-MW/BK	40	3500	88	6000	φ58x175	1.2

Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
ALL CODES	Yes	Yes		External	0-10	Yes	External

Photometric diagrams



Similar products

Denso TL



5W	350 Lm / 360 Lm / 380 Lm
10W	700 Lm / 720 Lm / 750 Lm
15W	1120 Lm / 1150 Lm / 1180 Lm
20W	1400 Lm / 1440 Lm / 1500 Lm

Atria



9W	680 Lm / 720 Lm / 740 Lm
16W	1100 Lm / 1280 Lm / 1350 Lm
22W	1580 Lm / 1680 Lm / 1780 Lm
30W	2120 Lm / 2300 Lm / 2400 Lm

Dolux



9W	820 Lm / 840 Lm / 855 Lm
15W	1380 Lm / 1395 Lm / 1425 Lm
18W	1650 Lm / 1680 Lm / 1710 Lm
25W	2300 Lm / 2325 Lm / 2375 Lm
35W	3220 Lm / 3255 Lm / 3325 Lm

Antares



20W	1550 Lm / 1610 Lm / 1650 Lm
------------	-----------------------------