

BOLL



Power^[W] / Luminosity^[Lm]

- 20 W > 1800 Lm



General information

- Mounting type: Applied
- Type LED: COB, SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +40
- UGR: <19
- CRI: >70
- PF: >0.9
- Angle: 360

Applications

- Outdoor, Ornamental, Gardens and Parks Lighting

Description

- The Bollard LED Boll perfectly replace traditional fixtures.
- It is an outdoor light fixture for use in pathways or gardens, made of high quality materials, finished to meet the highest customer requirements.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; high stability of continuous operation.

Body & Optics

- Body in pure aluminium, cast and finished, electrostatically painted.
- PMMA disperser, matte milky-white, finely textured.



IP65 IK06

BOLL

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
BOLL2090WW-BK	20	1800	90	3000K	120x900	3.5
BOLL2090NW-BK	20	1800	90	4000K	120x900	3.5
BOLL2090W-BK	20	1800	90	6000K	120x900	3.5
BOLL20120WW-BK	20	1800	90	3000K	120x1200	4.1
BOLL20120NW-BK	20	1800	90	4000K	120x1200	4.1
BOLL20120W-BK	20	1800	90	6000K	120x1200	4.1

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	NA	NA	NA