

# CANCO EDGE

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 50 W > 4500 Lm
- 75 W > 6750 Lm



## General information

---

- Mounting type: Suspended, applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +50
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 120

## Applications

---

- Commercial, Residential, Office, Horeca, Medical lighting

## Description

---

- The Cancó Edge lighting system can replace traditional fixtures perfectly.
- Thanks to the light guide diffuser, the lamp has a uniform and efficient light beam, low glare, low dazzle factor and excellent eye protection.

## Benefits

---

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

## Body & Optics

---

- Body in pure aluminium, cast and finished, electrostatically painted.
- PMMA disperser, matte milky-white

# CANCO EDGE

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
CNCE50W-WH/BK/S	50	4500	90	6000K	Φ860x60x68	4.2
CNCE50NW-WH/BK/S	50	4500	90	4000K	Φ860x60x68	4.2
CNCE50WW-WH/BK/S	50	4500	90	3000K	Φ860x60x68	4.2
CNCE75W-WH/BK/S	75	6750	90	6000K	Φ1200x60x68	6.8
CNCE75NW-WH/BK/S	75	6750	90	4000K	Φ1200x60x68	6.8
CNCE75WW-WH/BK/S	75	6750	90	3000K	Φ1200x60x68	6.8

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	Yes	Yes	NA	External	External	External	External