

# DALIA



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

- 10 W > 1500 Lm
- 20 W > 2500 Lm



## General information

- Mounting type: On a magnetic rail
- Type LED: COB
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +45
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 24/40

## Applications

- Commercial, Residential, Office, Horeca, Medical lighting

## Description

- A lighting system with a modern design and great visual impact, on magnetic rail, ensuring remarkable elegance and ease of installation.

## Benefits

- Very easy assembly, countless adjustment possibilities.

## Body & Optics

- Aluminium alloy body, cast and finished, electrostatically painted matt white, grey or black.
- Transparent, tempered, PC or glass disperser.

# DALIA

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
DAL10W-WH/BK	10	1500		6000K	175x156x40	0.8
DAL10NW-WH/BK	10	1500		4000K	175x156x40	0.8
DAL10WW-WH/BK	10	1500		3000K	175x156x40	0.8
DAL20W-WH/BK	20	2500		6000K	175x174x50	1
DAL20NW-WH/BK	20	2500		4000K	175x174x50	1
DAL20WW-WH/BK	20	2500		3000K	175x174x50	1

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	NA	Yes	Yes	Yes	NA

## Accessories



L connector



I connector



X connector



Rail 1m



Rail 2m