













Denso

5 W	350 Lm / 360 Lm / 370 Lm			
10 W	700 Lm / 720 Lm / 750 Lm			
15 W	1120 Lm / 1150 Lm / 1180 Lm			
20 W	1550 Lm / 1580 Lm / 1620 Lm			



Applications

Commercial / Office / Conference Halls and Classrooms / Medical / Advertising

Description

Denso TL is downlight round LED lighting which can perfectly replace conventional background recessed light sources.

Unique and sleek design.

Advantages

Low light pollution, excellent eye protection.

Fitting

Fitting made of cast and finished aluminium alloy, frosted-white, grey or black powder-coated.

Optics

Transparent and tempered PC or glass lens.

General Information

Mounting type: Suspended, Surface-mounted, Flush-mounted

LED type: COB

Voltage: 110-277 VAC / 50 Hz

Operating temperature: -10 / +45

UGR: <19

CRI: >80

PF: >0.95

Angle: 12/24/40


Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm / W]	Colour Temp. ^[K]	Dimensions ^[mm]	Weight ^[kg]
DS05WW-MW/S/BK	5	350	70	3000	φ55x92 / φ50	0.4
DS05NW-MW/S/BK	5	360	72	4000	φ55x92 / φ50	0.4
DS05W-MW/S/BK	5	370	74	6000	φ55x92 / φ50	0.4
DS10WW-MW/S/BK	10	700	70	3000	φ76x99 / φ70	0.5
DS10NW-MW/S/BK	10	720	72	4000	φ76x99 / φ70	0.5
DS10W-MW/S/BK	10	750	75	6000	φ76x99 / φ70	0.5
DS15WW-MW/S/BK	15	1120	75	3000	φ92X117 / φ85	0.65
DS15NW-MW/S/BK	15	1150	77	4000	φ92X117 / φ85	0.65
DS15W-MW/S/BK	15	1180	79	6000	φ92X117 / φ85	0.65
DS20WW-MW/S/BK	20	1550	78	3000	φ128X128 / φ122	0.75
DS20NW-MW/S/BK	20	1580	79	4000	φ128X128 / φ122	0.75
DS20W-MW/S/BK	20	1620	81	6000	φ128X128 / φ 122	0.75

Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Driver dimensions	DALI Driver	Sensor
ALL CODES			YES	External	0-10	YES	External

Photometric diagrams



Similar products

Stella



8 W	420 Lm / 490 Lm / 500 Lm
12W	740 Lm / 850 Lm / 870 Lm
18W	1220 Lm / 1370 Lm / 1400 Lm
24W	1260 Lm / 1470 Lm / 1500 Lm
30W	2240 Lm / 2520 Lm / 2620 Lm

Atria



9 W	680 Lm / 720 Lm / 740 Lm
16 W	1100 Lm / 1280 Lm / 1350 Lm
22 W	1580 Lm / 1680 Lm / 1780 Lm
30 W	2120 Lm / 2300 Lm / 2400 Lm

Dolux



9 W	820 Lm / 840 Lm / 855 Lm
15 W	1380 Lm / 1395 Lm / 1425 Lm
18W	1650 Lm / 1680 Lm / 1710 Lm
25 W	2300 Lm / 2325 Lm / 2375 Lm
35 W	3220 Lm / 3255 Lm / 3325 Lm

Nucleo



5 W	410 Lm / 10W 820 Lm
15 W	1700 Lm / 20W 1720 Lm