


# EDU-BL

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 36 W > 3000 Lm 

## General information

---

- Mounting type: Suspended, applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: 0 / +40
- UGR: <16
- CRI: >80
- PF: >0.95
- Angle: 85

## Applications

---

- Educational Lighting - Classrooms

## Description

---

- Luminaire exhibiting excellent uniformity of light, low blue light towards 0 - rating RG0; - UGR < 16; - CRI > 90.
- No danger of yellowing over time.

## Benefits

---

- Up to 80% less consumption than traditional appliances.
- Attractive, high-quality appearance.

## Body & Optics

---

- Body made of extruded, pure, die-cast and pressure-finished aluminium.
- PC/PS diffuser with striations for uniform illumination

# EDU-BL

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
ED36WW-BL	36	3000	83	3000K	1200x300x45	3.1
ED36NW-BL	36	3000	83	4000K	1200x300x45	3.1
ED36W-BL	36	3000	83	6000K	1200x300x45	3.1

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	Yes	Yes	NA	External	Yes	Yes	Yes