

EDU-EGL



Power^[W] / Luminosity^[Lm]

- 40 W > 3600 Lm



General information

- Mounting type: Suspended, applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: 0 / +40
- UGR: <16
- CRI: >80
- PF: >0.95
- Angle: 85

Applications

- Educational Lighting - Classrooms

Description

- Luminaire exhibiting excellent uniformity of light, low blue light towards 0 - rating RG0; - UGR < 16; - CRI > 90.
- No danger of yellowing over time.

Benefits

- Up to 80% less consumption than traditional appliances.
- Attractive, high-quality appearance.

Body & Optics

- Body made of extruded, pure, die-cast and pressure-finished aluminium.
- PC/PS diffuser with striations for uniform illumination

EDU-EGL

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
ED40WW-EDGL	40	3600	90	3000K	1200x300x20	3.3
ED40NW-EDGL	40	3600	90	4000K	1200x300x20	3.3
ED40W-EDGL	40	3600	90	6000K	1200x300x20	3.3

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	Yes	Yes	NA	External	Yes	Yes	Yes