

EuroStar

- 30 W 3900 Lm
- 50 W 6500 Lm
- 70 W 9100 Lm
- 90 W 11700 Lm
- 100 W 13000 Lm
- 120 W 15600 Lm
- 150 W 19500 Lm
- 180 W 23400 Lm



Applications

Public / Street / Perimeters / Parking lighting

Fitting

Fitting made of die cast and finished pure aluminium.

Description

EuroStar is a street LED lighting device providing an efficient and aesthetic alternative to conventional street lighting.

Optics

Polycarbonate or glass diffuser with angle lenses for perimeter lighting.
Impact, moisture and dust-resistant.

Advantages

Quality, adjustable and very efficient lighting.
Reduced energy consumption by up to 80% compared to conventional light sources.

General Information

LED type: SMD
Voltage: 110-277 VAC / 50-60 Hz
Operating temperature: -40 / +60
UGR: <19
CRI: >70
PF: >0.90
Angle: 145


Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm / W]	Colour Temp.	Dimensions ^[mm]	Weight ^[kg]
ES30W-S	30	3900	130	6000	560x320x140	7.5
ES50W-S	50	6500	130	6000	560x320x140	7.5
ES70W-S	70	9100	130	6000	560x320x140	7.8
ES90W-S	90	11700	130	6000	560x320x140	7.8
ES100W-S	100	13000	130	6000	680x390x160	10.2
ES120W-S	120	15600	130	6000	680x390x160	10.2
ES150W-S	150	19500	130	6000	680x390x160	10.5
ES180W-S	180	23400	130	6000	680x390x160	10.5

Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
ALL CODES					0-10	YES	External

Photometric diagrams



Similar products

Stockholm



30W >110 Lm/W

50W >110 Lm/W

100W >110 Lm/W

150W >110 Lm/W

Hagen



50W >110 Lm/W

80W >110 Lm/W

100W >110 Lm/W

120W >110 Lm/W

Nice



30W >100 Lm/W

50W >100 Lm/W

100W >100 Lm/W

120W >100 Lm/W

Dresden



57W >105 Lm/W