

FORAS



Power^[W] / Luminosity^[Lm]

- 5 W > 425 Lm
- 7 W > 595 Lm
- 10 W > 850 Lm
- 12 W > 1020 Lm
- 15 W > 1275 Lm



General information

- Mounting type: Applied
- Type LED: COB
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 15/36/60

Applications

- Outdoor, Ornamental, Gardens and Parks Lighting

Description

- The Foras LED spotlight can perfectly replace traditional fixtures.
- It is an outdoor lighting fixture, applicable on walkways or walls made of high quality materials, finished to meet the highest customer demands.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; high stability of continuous operation.

Body & Optics

- Body in pure aluminium, cast and finished, electrostatically painted.
- Transparent PMMA disperser



IP66 IK07

FORAS

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
FOR05W-BK	5	425	85	6000K	70x125	0.6
FOR05NW-BK	5	425	85	4000K	70x125	0.6
FOR05WW-BK	5	425	85	3000K	70x125	0.6
FOR07W-BK	7	595	85	6000K	70x125	0.6
FOR07NW-BK	7	595	85	4000K	70x125	0.6
FOR07WW-BK	7	595	85	3000K	70x125	0.6
FOR10W-BK	10	850	85	6000K	80x144	0.8
FOR10NW-BK	10	850	85	4000K	80x144	0.8
FOR10WW-BK	10	850	85	3000K	80x144	0.8
FOR12W-BK	12	1020	85	6000K	80x144	0.8
FOR12NW-BK	12	1020	85	4000K	80x144	0.8
FOR12WW-BK	12	1020	85	3000K	80x144	0.8
FOR15W-BK	15	1275	85	6000K	80x144	0.8
FOR15NW-BK	15	1275	85	4000K	80x144	0.8
FOR15WW-BK	15	1275	85	3000K	80x144	0.8

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	NA	NA	External