

GLAM SQUARE



Power^[W] / Luminosity^[Lm]

- 24 W > 2640 Lm

General information

- Mounting type: Applied
- Type LED: SMD
- Voltage: 100-240 VAC / 50-60Hz
- Operational temperature: -5 / +35
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 100

Applications

- Commercial, Residential, Office, Horeca, Medical lighting

Description

- Applied fixture with direct lighting, with the possibility of changing the intensity and colour of the light from warm white to natural white and cool white, or with a natural white colour.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Controls to suit the user's mood.

Body & Optics

- Premium quality polycarbonate body.
- Transparent polycarbonate disperser.
- Shock, moisture and dust resistant.
- Premium quality.

GLAM SQUARE

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
GLAMSQ24NW-WH	24	2640	110	4000K	Φ320x57	1.3

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
GLAMSQ24NW-WH	NA	Yes	NA	External	Yes	NA	NA