

GLOBUS



GLO140W/NW/WW-S/BK



GLO240W/NW/WW-S/BK



GLO340W/NW/WW-S/BK

Power^[W] / Luminosity^[Lm]

- 40 W > 4800 Lm



General information

- Mounting type: On the end of a pole
- Type LED: SMD
- Voltage: 90-305 V
- Operational temperature: -35 / +55
- UGR:
- CRI: >70
- PF:
- Angle: 360

Applications

- Street lighting, perimeter lighting, parks

Description

- Decorative luminaire for lighting outdoor areas, especially gardens, parks, pathways.
- Provides very pleasant lighting.

Benefits

- Provides quality, uniform, controllable and highly efficient lighting.
- Up to 80% less consumption than traditional appliances.

Body & Optics

- Body made of die-cast and pressure-finished aluminium.
- Shock, moisture and dust resistant.
- Polycarbonate diffuser with efficient optics.

GLOBUS

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
GLO140W/NW/WW-S/BK	40	4800	120	3000K	500X563	11.8
GLO240W/NW/WW-S/BK	40	4800	120	4000K	500X563	11.8
GLO340W/NW/WW-S/BK	40	4800	120	6000K	500X563	11.8

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	NA	NA	Yes	Yes	NA