

Inka

4W
7W



Scope of application

Safety / Emergency / Evacuation /
Hydrants highlighting / Public lighting

Description

Inka is an emergency luminaire with dust and moisture protection, provided with SMD 3528 LEDs for wall mounting.

Advantages

3-hour operating autonomy in permanent or non-permanent operating conditions.

Fitting

Moisture, dust and impact-resistant finished polycarbonate fitting.

General Information

Mounting type: Flush-mounted
LED type: SMD
Voltage: 200-240 VAC / 50 Hz
Operating temperature: -5 / +40
UGR: NA
CRI: NA
PF: NA
Angle: 120


Technical data


Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm / W]	Colour Temp. ^[K]	Dimensions ^[mm]	Weight ^[kg]
IK04-H3/2-LR/UD/H	4	NA	NA	4000-5000K	420x164x169	0.8
IK07-H3/2-LR/UD/HBK	7	NA	NA	4000-5000K	420x164x169	0.8

Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
ALL CODES			Yes	External			

Similar products

Orion	
	3W
	7W

Mobility	
	2W

Kasiopeea	
	2W

Swing	
	2W