

Jade

10W 909 Lm / 915 Lm / 991 Lm
15W 1316 Lm / 1392 Lm / 1441 Lm
20W 1688 Lm / 1785 Lm / 1807 Lm



Scope of application

Commercial / Office / Conference Halls /
Classrooms / Medical / Advertising

Description

Jade is a downlight round LED lighting,
which can perfectly replace conventional
background recessed light sources.

Advantages

Low blindness factor, excellent eye
protection.

Fitting

Fitting made of cast and finished aluminium
alloy, frosted-white powder coated.

Optics

Transparent and tempered PC or glass
lens.

General Information

Mounting type: Suspended, Surface-
mounted, Flush-mounted
LED type: SMD
Voltage: 100-240 VAC / 50 Hz
Operating temperature: -10 / +45
UGR: <19
CRI: >80
PF: >0.95
Angle: 90/100

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm / W]	Colour Temp. ^[K]	Dimensions ^[mm]	Weight ^[kg]
JD10WW-MWK	10	909	91	3000	φ132*132*83/φ105	0.2
JD10NW-MW	10	915	92	4000	φ132*132*83/φ105	0.2
JD10W-MW	10	991	99	6500	φ132*132*83/φ105	0.2
JD15WW-MW	15	1316	88	3000	φ270*270*85/φ155	0.3
JD15NW-MW	15	1392	93	4000	φ270*270*85/φ155	0.3
JD15W-MW	15	1441	96	6500	φ270*270*85/φ155	0.3
JD20WW-MW	20	1688	84	3000	φ183*183*88/φ205	0.45
JD20NW-MW	20	1785	89	4000	φ183*183*88/φ205	0.45
JD20W-MW	20	1807	90	6500	φ183*183*88/φ205	0.45

Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
ALL CODES			Yes	External	0-10	Yes	External

Photometric diagrams



Similar products

Stella



8W	420 Lm / 490 Lm / 500 Lm
12W	740 Lm / 850 Lm / 870 Lm
18W	1220 Lm / 1370 Lm / 1400 Lm
24W	1260 Lm / 1470 Lm / 1500 Lm
30W	2240 Lm / 2520 Lm / 2620 Lm

Atria



9W	680 Lm / 720 Lm / 740 Lm
16W	1100 Lm / 1280 Lm / 1350 Lm
22W	1580 Lm / 1680 Lm / 1780 Lm
30W	2120 Lm / 2300 Lm / 2400 Lm

Dolux



9W	820 Lm / 840 Lm / 855 Lm
15W	1380 Lm / 1395 Lm / 1425 Lm
18W	1650 Lm / 1680 Lm / 1710 Lm
25W	2300 Lm / 2325 Lm / 2375 Lm
35W	3220 Lm / 3255 Lm / 3325 Lm

Nucleo



5W	410 Lm / 10W 820 Lm
15W	1700 Lm / 20W 1720 Lm