

# JULIUS 1

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 36 W > 3060 Lm
- 50 W > 4250 Lm



## General information

---

- Mounting type: Applied
- Type LED: SMD
- Voltage: 100-305 VAC / 50-60Hz
- Operational temperature: -20 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 90

## Applications

---

- Architectural lighting

## Description

---

- Julius 1 is an outdoor LED floodlight that can be used for simplified architectural lighting of buildings.
- It is made of high quality materials, finished to meet the highest customer demands.

## Benefits

---

- Modern and simple design
- Simple structure, easy to install.
- It saves energy compared to traditional appliances and is environmentally friendly.

## Body & Optics

---

- Aluminium alloy body, cast and finished, electrostatically painted, black.
- Transparent, tempered, PC disperser.



IP65 IK06

# JULIUS 1

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
JUL36WW-BK	36	3060	85	3000K	153x180x89	1.8
JUL36NW-BK	36	3060	85	4000K	153x180x89	1.8
JUL36W-BK	36	3060	85	6000K	153x180x89	1.8
JUL50WW-BK	50	4250	85	3000K	153x180x89	1.8
JUL50NW-BK	50	4250	85	4000K	153x180x89	1.8
JUL50W-BK	50	4250	85	6000K	153x180x89	1.8

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	Yes	Yes	NA