

JULIUS 3



Power^[W] / Luminosity^[Lm]

- 108 W > 9180 Lm
- 150 W > 12750 Lm



General information

- Mounting type: Applied
- Type LED: SMD
- Voltage: 100-305 VAC / 50-60Hz
- Operational temperature: -20 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 90

Applications

- Architectural lighting

Description

- Julius 3 is an outdoor LED floodlight that can be used for simplified architectural lighting of buildings.
- It is made of high quality materials, finished to meet the highest customer demands.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- It saves energy compared to traditional appliances and is environmentally friendly.

Body & Optics

- Aluminium alloy body, cast and finished, electrostatically painted, black.
- Transparent, tempered, PC disperser.

JULIUS 3

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
JUL108WW-BK	108	9180	85	3000K	150x470x89	4.9
JUL108NW-BK	108	9180	85	4000K	150x470x89	4.9
JUL108W-BK	108	9180	85	6000K	150x470x89	4.9
JUL150WW-BK	150	12750	85	3000K	150x470x89	4.9
JUL150NW-BK	150	12750	85	4000K	150x470x89	4.9
JUL150W-BK	150	12750	85	6000K	150x470x89	4.9

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	Yes	Yes	NA