

# JULIUS 4B

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 144 W > 12240 Lm
- 200 W > 17000 Lm



## General information

---

- Mounting type: Applied
- Type LED: SMD
- Voltage: 100-305 VAC / 50-60Hz
- Operational temperature: -20 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 90

## Applications

---

- Architectural lighting

## Description

---

- The Julius 4B is an outdoor LED floodlight that can be used for simplified architectural lighting of buildings.
- It is made of high quality materials, finished to meet the highest customer demands.

## Benefits

---

- Modern and simple design
- Simple structure, easy to install.
- It saves energy compared to traditional appliances and is environmentally friendly.

## Body & Optics

---

- Aluminium alloy body, cast and finished, electrostatically painted, black.
- Transparent, tempered, PC disperser.

# JULIUS 4B

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
JULB144WW-BK	144	12240	85	3000K	300x330x89	6.8
JULB144NW-BK	144	12240	85	4000K	300x330x89	6.8
JULB144W-BK	144	12240	85	6000K	300x330x89	6.8
JULB200WW-BK	200	17000	85	3000K	300x330x89	6.8
JULB200NW-BK	200	17000	85	4000K	300x330x89	6.8
JULB200W-BK	200	17000	85	6000K	300x330x89	6.8

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	Yes	Yes	NA