

# JURA



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

- 15 W > 1261 Lm
- 20 W > 1811 Lm
- 30 W > 2748 Lm
- 40 W > 3795 Lm

## General information

- Mounting type: Embedded
- Type LED: COB
- Voltage: 100-240 VAC / 50-60Hz
- Operational temperature: -10 / +40
- UGR: <19
- CRI: >80
- PF: >0.95
- Angle: 60

## Applications

- Comercial, Horeca, Office Lighting

## Description

- The Jura lighting fixture has an IP65 moisture protection rating, so it can be mounted with confidence in high humidity environments.
- It has a modern and versatile design and can be used in various office, industrial, residential or commercial applications.

## Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

## Body & Optics

- Body made of die-cast and pressure-finished extruded aluminium.
- Transparent polycarbonate disperser.
- Shock, moisture and dust resistant.
- Premium quality.

# JURA

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
JR15WW-MW	15	1261	84	3000K	Φ110x60 - Φ92	0.4
JR15NW-MW	15	1400	93	4000K	Φ110x60 - Φ92	0.4
JR15W-MW	15	1444	96	6000K	Φ110x60 - Φ92	0.4
JR20WW-MW	20	1811	91	3000K	Φ127x70 - Φ112	0.6
JR20NW-MW	20	1830	92	4000K	Φ127x70 - Φ112	0.6
JR20W-MW	20	1840	92	6000K	Φ127x70 - Φ112	0.6
JR30WW-MW	30	2748	92	3000K	Φ164x81 - Φ150	0.9
JR30NW-MW	30	3110	104	4000K	Φ164x81 - Φ150	0.9
JR30W-MW	30	2927	98	6000K	Φ164x81 - Φ150	0.9
JR40WW-MW	40	3795	95	3000K	Φ220x90 - Φ200	1.5
JR40NW-MW	40	4217	105	4000K	Φ220x90 - Φ200	1.5
JR40W-MW	40	4080	102	6000K	Φ220x90 - Φ200	1.5

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	Yes	External	NA	NA	NA