

KALA



Power^[W] / Luminosity^[Lm]

- 8 W > 1500 Lm



General information

- Mounting type: On a magnetic rail
- Type LED: COB
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +45
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 22/52

Applications

- Commercial, Residential, Office, Horeca, Medical lighting

Description

- Kala is a high-efficiency COB LED technology luminaire with magnetic rail mounting.
- Simple and attractive appearance.
- Single cast aluminium alloy luminaire with good heat dissipation effect.
- High temperature resistant transparent glass.

Benefits

- Very easy assembly, countless adjustment possibilities.

Body & Optics

- Aluminium alloy body, cast and finished, electrostatically painted matt white, grey or black.
- Transparent, tempered, PC or glass disperser.

KALA

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
KLA8W-WH/BK	8	1500		6000K	175x113x79	0.7
KLA8NW-WH/BK	8	1500		4000K	175x113x79	0.7
KLA8WW-WH/BK	8	1500		3000K	175x113x79	0.7

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	NA	Yes	Yes	Yes	NA

Accessories



L connector



I connector



X connector



Rail 1m



Rail 2m