













Kasa

10W	750 Lm / 770 Lm / 780 Lm			
20W	1500 Lm / 1530 Lm / 1570 Lm			
30W	2250 Lm / 2300 Lm / 2330 Lm			
35W	2620 Lm / 2700 Lm / 2720 Lm			



Scope of application

Commercial / Office / Conference Halls and Classrooms / Medical / Advertising

Description

Kasa is a light fitting with high-efficiency COB LED technology, adjustable on two axes.

Simple and sleek look.

Lighting device made of unit cast aluminium alloy, with a good thermal dissipation effect.

High-temperature transparent resistant glass.

Advantages

High luminous efficiency and energy saving.

Fitting

Fitting made of cast and finished aluminium alloy, frosted white or black powder coated.

Optics

Transparent and tempered PMMA, PC or glass lens.

General Information

Mounting type: Suspended, Surface-mounted, Flush-mounted

LED type: COB

Voltage: 110-277 VAC / 50 Hz

Operating temperature: -10 / +45

UGR: <19

CRI: >80

PF: >0.95

Angle: 12/24/40


Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm / W]	Colour Temp. ^[K]	Dimensions ^[mm]	Weight ^[kg]
KS10WW-MW/S/BK	10	750	75	3000	208x50x70	0.6
KS10NW-MW/S/BK	10	770	77	4000	208x50x70	0.6
KS10W-MW/S/BK	10	780	78	6000	208x50x70	0.6
KS20WW-MW/S/BK	20	1500	75	3000	229x60x77	0.75
KS20NW-MW/S/BK	20	1530	77	4000	229x60x77	0.75
KS20W-MW/S/BK	20	1570	79	6000	229x60x77	0.75
KS30WW-MW/S/BK	30	2250	75	3000	249x71x88	0.9
KS30NW-MW/S/BK	30	2300	77	4000	249x71x88	0.9
KS30W-MW/S/BK	30	2330	78	6000	249x71x88	0.9
KS35WW-MW/S/BK	35	2620	75	3000	252x83x100	1
KS35NW-MW/S/BK	35	2700	77	4000	252x83x100	1
KS35W-MW/S/BK	35	2720	78	6000	252x83x100	1

Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
ALL CODES					0-10	Yes	External

Photometric diagrams



Similar products

Selene



10W	800 Lm / 830 Lm / 850 Lm
20W	1600 Lm / 1640 Lm / 1650 Lm
30W	2400 Lm / 2450 Lm / 2480 Lm
40W	3200 Lm / 3280 Lm / 3300 Lm

Vero



18W	1500 Lm
30W	2250 Lm
35W	2620 Lm

Stil



30W	2150 Lm / 2400 Lm / 2650 Lm
------------	-----------------------------

Optional equipment

Filters

