

LUNAR



Power^[W] / Luminosity^[Lm]

- 9 W > 315 Lm
- 15 W > 525 Lm
- 18 W > 630 Lm
- 30 W > 1050 Lm
- 36 W > 1260 Lm



General information

- Mounting type: Embedded
- Type LED: SMD
- Voltage: 124 VDC
- Operational temperature: -20 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 120

Applications

- Outdoor, Ornamental, Gardens and Parks Lighting

Description

- The Lunar LED luminaire is a linear outdoor lighting fixture, recessed into exterior walls, made of high quality, highly durable materials and finished to meet the highest customer demands.
- Can be used to create architectural lighting scenes on buildings

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

Body & Optics

- Aluminium body, cast and finished, electrostatically painted.
- Transparent PMMA disperser

LUNAR

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
LNR09W-BK	9	315	35	6000K	300x45x80	1.6
LNR09NW-BK	9	315	35	4000K	300x45x80	1.6
LNR09WW-BK	9	315	35	3000K	300x45x80	1.6
LNR15W-BK	15	525	35	6000K	500x45x80	1.9
LNR15NW-BK	15	525	35	4000K	500x45x80	1.9
LNR15WW-BK	15	525	35	3000K	500x45x80	1.9
LNR18W-BK	18	630	35	6000K	600x45x80	2.1
LNR18NW-BK	18	630	35	4000K	600x45x80	2.1
LNR18WW-BK	18	630	35	3000K	600x45x80	2.1
LNR30W-BK	30	1050	35	6000K	1000x45x80	2.9
LNR30NW-BK	30	1050	35	4000K	1000x45x80	2.9
LNR30WW-BK	30	1050	35	3000K	1000x45x80	2.9
LNR36W-BK	36	1260	35	6000K	1200x45x80	3.2
LNR36NW-BK	36	1260	35	4000K	1200x45x80	3.2
LNR36WW-BK	36	1260	35	3000K	1200x45x80	3.2

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	Yes	NA	Yes	Yes	NA