

MANOR SPIKE



Power^[W] / Luminosity^[Lm]

- 13 W > 1000 Lm
- 20 W > 1800 Lm



General information

- Mounting type: Applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -20 / +45
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 90

Applications

- Outdoor, Ornamental, Gardens and Parks Lighting

Description

- Manor Spike is an outdoor, walkway luminaire made of high quality materials, finished to meet the highest customer demands.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- It saves energy compared to traditional appliances and is environmentally friendly.

Body & Optics

- Aluminium alloy body, cast and finished, electrostatically painted, black.
- Transparent, tempered, PC disperser.



IP65 IK06

MANOR SPIKE

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
MAN13WW-BK-SPK	13	1000	77	3000K	98x108x125	0.9
MAN13NW-BK-SPK	13	1000	77	4000K	98x108x125	0.9
MAN13W-BK-SPK	13	1000	77	6000K	98x108x125	0.9
MAN20WW-BK-SPK	20	1800	90	3000K	122x131x158	1.1
MAN20NW-BK-SPK	20	1800	90	4000K	122x131x158	1.1
MAN20W-BK-SPK	20	1800	90	6000K	122x131x158	1.1

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	NA	NA	NA	NA	NA