

MARS SQUARE



Power^[W] / Luminosity^[Lm]

- 18 W > 1530 Lm

General information

- Mounting type: Applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +40
- UGR: <19
- CRI: >80
- PF: >0.5
- Angle: 120/360

Applications

- Ceiling and wall fixtures

Description

- The wall mounted LED Mars Square can replace traditional fixtures perfectly.
- Thanks to the light guide disperser, Mars Square has a uniform and efficient light beam, low glare, low dazzle factor and excellent eye protection.

Benefits

- Indirect lighting behind the mounting point, producing a unique optical effect

Body & Optics

- White PP body
- PS disperser, matte milky-white, finely textured

MARS SQUARE

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
MARS18W-WH-SQUARE	18	1530	85	6000K	Φ280x280x50	0.85
MARS18NW-WH-SQUARE	18	1530	85	4000K	Φ280x280x50	0.85
MARS18WW-WH-SQUARE	18	1530	85	3000K	Φ280x280x50	0.85