

# Mobility

2W



## Scope of application

Safety / Emergency / Evacuation / Hydrants highlighting / Public lighting

## Description

Safety lighting fitting, equipped with SMD 3528 LEDs for wall or ceiling mounting, with dust and moisture protection.

## Advantages

2-3 hours operating autonomy in permanent or non-permanent operating conditions.

## Fitting

Moisture, dust and impact-resistant finished polycarbonate fitting.

## General Information

Mounting type: Suspended,  
Surface-mounted  
LED type: SMD  
Voltage: 220-240 VAC / 50 Hz  
Operating temperature: -10 / +35


## Technical data


Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm / W]</sup>	Colour Temp. <sup>[K]</sup>	Dimensions <sup>[mm]</sup>	Weight <sup>[kg]</sup>
MB02-H3-LR/UD/H	2	NA		NA	310x230x35	0.9


## Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
MB02	YES	YES		YES	NA	NA	NA

## Similar products

Kasiopeea
 2W

Orion
 3W
7W

Swing
 2W

Orion Clip
 3W