

MOON ROUND



Power^[W] / Luminosity^[Lm]

- 18 W > 1620 Lm

General information

- Mounting type: Applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 130

Applications

- Commercial, Residential, Office, Horeca, Medical lighting

Description

- The wall mounted LED Moon can replace traditional fixtures perfectly.
- Thanks to the light guide diffuser, Moon has a uniform and efficient light beam, low glare, low dazzle factor and excellent eye protection.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

Body & Optics

- Metal body, electrostatically painted.
- PMMA disperser, matte milky-white, finely textured.

MOON ROUND

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
MOON18W-WH	18	1620	90	6000K	Φ320x80	1.1
MOON18NW-WH	18	1620	90	4000K	Φ320x80	1.1
MOON18WW-WH	18	1620	90	3000K	Φ320x80	1.1

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	NA	NA	External