

# MOON SQUARE

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 18 W > 1620 Lm

## General information

---

- Mounting type: Applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 130

## Applications

---

- Commercial, Residential, Office, Horeca, Medical lighting

## Description

---

- The wall mounted LED Moon can replace traditional fixtures perfectly.
- Thanks to the light guide diffuser, Moon has a uniform and efficient light beam, low glare, low dazzle factor and excellent eye protection.

## Benefits

---

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

## Body & Optics

---

- Metal body, electrostatically painted.
- PMMA disperser, matte milky-white, finely textured.

# MOON SQUARE

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
MOON18W-WH-SQ	18	1620	90	6000K	300x300x80	0.9
MOON18NW-WH-SQ	18	1620	90	4000K	300x300x80	0.9
MOON18WW-WH-SQ	18	1620	90	3000K	300x300x80	0.9

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	NA	NA	External