

# Nice

**40W** >4200 Lm  
**60W** >6300 Lm  
**100W** >10500 Lm



## Scope of application

Public / Street / Perimetral / Parking lighting

## Description

The public lighting fittings of Nice series provide an efficient and aesthetic alternative to conventional industrial lighting.

Nice is distinguished by its quality, adjustable and very efficient lighting, under reduced energy consumption by up to 80% compared to conventional light sources.

Its modern shape offers a sleek quality alternative.

## Advantages

Easy mounting on a bracket with an adjustable arm.

Long service life.

Optimum, economic, easily controllable lighting.

It does not contain chemicals that could harm the environment.

## Fitting

Fitting of cast and finished aluminium, grey-silver powder coated.

## Optics

Polycarbonate or glass diffuser with angle lenses for perimetral lighting.

## General Information

LED type: SMD

Voltage: 90-305 VAC / 50-60 Hz

Operating temperature: -30 / +55

UGR: <19

CRI: >70

PF: >0.9

Angle: 150


## Technical data

| Code        | Power <sup>[W]</sup> | Luminosity <sup>[Lm]</sup> | Efficiency <sup>[Lm / W]</sup> | Colour Temp. <sup>[K]</sup> | Dimensions <sup>[mm]</sup> | Weight <sup>[kg]</sup> |
|-------------|----------------------|----------------------------|--------------------------------|-----------------------------|----------------------------|------------------------|
| NS40W-S/Bk  | 40                   | >4200                      | >105                           | 3000/4000/6500              | 557x358x155                | 2.8                    |
| NS60W-S/Bk  | 60                   | >6300                      | >105                           | 3000/4000/6500              | 635x175x305                | 4.6                    |
| NS100W-S/Bk | 100                  | >10500                     | >105                           | 3000/4000/6500              | 800x370x220                | 10                     |

## Accessories

| Product code | Suspension system | Application system | Embedding clips | Emergency kit | 0-10V Dim. driver | DALI Driver | Sensor   |
|--------------|-------------------|--------------------|-----------------|---------------|-------------------|-------------|----------|
| ALL CODES    |                   |                    |                 |               | 0-10              |             | External |

## Photometric diagrams



## Similar products

### Monaco H



|             |          |
|-------------|----------|
| <b>40W</b>  | >95 Lm/W |
| <b>75W</b>  | >95 Lm/W |
| <b>100W</b> | >95 Lm/W |
| <b>150W</b> | >95 Lm/W |

### Hagen



|             |           |
|-------------|-----------|
| <b>50W</b>  | >110 Lm/W |
| <b>80W</b>  | >110 Lm/W |
| <b>100W</b> | >110 Lm/W |
| <b>120W</b> | >110 Lm/W |

### Stockholm



|             |           |
|-------------|-----------|
| <b>30W</b>  | >105 Lm/W |
| <b>50W</b>  | >105 Lm/W |
| <b>100W</b> | >105 Lm/W |
| <b>120W</b> | >105 Lm/W |

### Dresden



|            |           |
|------------|-----------|
| <b>57W</b> | >105 Lm/W |
|------------|-----------|