

# NOR

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 11 W > 1100 Lm
- 20 W > 1800 Lm

## General information

---

- Mounting type: Applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50Hz / 4.8V 1800mAh Ni-Cd
- Operational temperature: -5 / +40
- Angle: 110

## Applications

---

- Office, comercial, industrial

## Description

---

- Nor is a permanent LED emergency luminaire for signalling exits and escape routes from industrial buildings, institutions and premises in the event of a power failure.
- Dust and moisture protected, equipped with SMD 3528 LEDs, for ceiling or wall mounting.

## Benefits

---

- 3 hours operating time, permanent or non-permanent operation.

## Body & Optics

---

- Body made of finished polycarbonate, dust and shock resistant.
- PC disperser, matte milky-white, finely textured.

# NOR

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
NR11-WH-3H	11	1100	100		Φ260x100	0.5
NR20-WH-3H	20	1800	90		Φ260x100	0.5

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	Yes	NA	Yes	External