

# ORBIT



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

- 25 W > 2275 Lm
- 38 W > 3458 Lm
- 50 W > 4550 Lm
- 63 W > 5733 Lm
- 75 W > 6825 Lm
- 94 W > 8554 Lm



## Description

- The LED Orbit lighting system can replace traditional fixtures perfectly.
- Thanks to the light guide diffuser, the lamp has a uniform and efficient light beam, low glare, low dazzle factor and excellent eye protection.

## General information

- Mounting type: Suspended
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +50
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 90

## Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

## Body & Optics

- Body in pure aluminium, cast and finished, electrostatically painted.
- PMMA disperser, matte milky-white

## Applications

- Commercial, Residential, Office, Horeca, Medical lighting

# ORBIT

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
ORB25W-WH/BK	25	2275	91	6000K	Φ400x25x60	3.1
ORB25NW-WH/BK	25	2275	91	4000K	Φ400x25x60	3.1
ORB25WW-WH/BK	25	2275	91	3000K	Φ400x25x60	3.1
ORB38W-WH/BK	38	3458	91	6000K	Φ600x25x60	3.9
ORB38NW-WH/BK	38	3458	91	4000K	Φ600x25x60	3.9
ORB38WW-WH/BK	38	3458	91	3000K	Φ600x25x60	3.9
ORB50W-WH/BK	50	4550	91	6000K	Φ800x25x60	5.7
ORB50NW-WH/BK	50	4550	91	4000K	Φ800x25x60	5.7
ORB50WW-WH/BK	50	4550	91	3000K	Φ800x25x60	5.7
ORB63W-WH/BK	63	5733	91	6000K	Φ1000x25x60	6.8
ORB63NW-WH/BK	63	5733	91	4000K	Φ1000x25x60	6.8
ORB63WW-WH/BK	63	5733	91	3000K	Φ1000x25x60	6.8
ORB75W-WH/BK	75	6825	91	6000K	Φ1200x25x60	7.2
ORB75NW-WH/BK	75	6825	91	4000K	Φ1200x25x60	7.2
ORB75WW-WH/BK	75	6825	91	3000K	Φ1200x25x60	7.2
ORB94W-WH/BK	94	8554	91	6000K	Φ1500x25x60	8.2
ORB94NW-WH/BK	94	8554	91	4000K	Φ1500x25x60	8.2
ORB94WW-WH/BK	94	8554	91	3000K	Φ1500x25x60	8.2

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	Yes	NA	NA	External	External	External	External