# **Orion**

**3W 7W** 





## Scope of application

Safety / Emergency / Evacuation / Hydrants highlighting / Public lighting

## **Description**

Permanent safety LED luminaire indicating the exit and evacuation routes from industrial buildings, institutions and premises.

## **Advantages**

2-3 hours operating autonomy in permanent or non-permanent operating conditions.

### **Fitting**

Fire-resistant, V0 high-quality polycarbonate fitting.

#### **General Information**

Mounting type: Surface-mounted

LED type: SMD

Voltage: 220-240 VAC / 50 Hz Operating temperature: -20 / +45







## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm / W]</sup>	Colour Temp.[k]	Dimensions <sup>[mm]</sup>	Weight <sup>[kg]</sup>
OR03-H3/2-LR/UD/H	3	NA		4000-5000	350x117x76	0.8
OR07-H3/2-LR/UD/H	7	NA		4000-5000	350x117x76	0.8

## Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
ALL CODES		YES		YES	NA	NA	NA

## Similar products



