

PEN



Power^[W] / Luminosity^[Lm]

- 10 W > 1530/1560/1580 Lm
- 20 W > 2550/2600/2630 Lm

General information

- Mounting type: On a magnetic rail
- Type LED: COB
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +45
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 20/40/60

Applications

- Commercial, Residential, Office, Horeca, Medical lighting

Description

- A lighting system with a modern design and great visual impact, on magnetic rail, ensuring remarkable elegance and ease of installation.

Benefits

- Very easy assembly, countless adjustment possibilities.

Body & Optics

- Aluminium alloy body, cast and finished, electrostatically painted matt white, grey or black.
- Transparent, tempered, PC or glass disperser.

PEN

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
PN10W-WH/BK	10	1580		6000K	1632x40	0.8
PN10NW-WH/BK	10	1560		4000K	1632x40	0.8
PN10WW-WH/BK	10	1530		3000K	1632x40	0.8
PN20W-WH/BK	20	2630		6000K	1650x50	0.9
PN20NW-WH/BK	20	2600		4000K	1650x50	0.9
PN20WW-WH/BK	20	2550		3000K	1650x50	0.9

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	Yes	NA	NA	NA	Yes	NA	NA

Accessories



L connector



I connector



X connector



Rail 1m



Rail 2m