

# REVOL

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 2 W > 110 Lm

## General information

---

- Mounting type: Applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50Hz / 3.6V 900mAh Ni-Cd
- Operational temperature: -5 / +40
- Angle: 110

## Applications

---

- Office, comercial, industrial

## Description

---

- Revol a permanent or non-permanent LED safety lighting fixture for signalling exits and escape routes from industrial buildings, institutions and premises.
- Equipped with LED SMD 3528.

## Benefits

---

- 3 hours operating time, permanent or non-permanent operation.

## Body & Optics

---

- Body made of finished polycarbonate, dust and shock resistant.
- PC disperser, matte milky-white, finely textured.

# REVOL

## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
RVL02-WH-3H	2	110	55		240x90x41	0.4

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	Yes	NA	NA	External