

Roll

2 W



Applications

Safety / Emergency / Evacuation / Hydrants highlighting / Public lighting

Description

Roll is a safety lighting fitting, endowed with SMD 3528 LEDs for wall mounting.

Permanent or non-permanent operating conditions.

Advantages

Dust and moisture protection.

2-3 hours of operating autonomy.

Fitting

Fitting made of polycarbonate.

General Information

Mounting type: Suspended, surface-mounted

LED type: SMD

Voltage: 220-240 VAC / 50Hz

Operating temperature: -5 / +40

UGR: NA

CRI: NA

PF: NA

Angle: NA


Technical data


| Code | Power ^[W] | Luminosity ^[Lm] | Efficiency ^[Lm] | Colour Temp. | Dimensions ^[mm] | Weight ^[kg] |
|-------------|----------------------|----------------------------|----------------------------|--------------|----------------------------|------------------------|
| SW02-H3-LR/ | 2 | NA | NA | NA | 335x240x25 | 0.9 |

Accessories


| Product code | Suspension system | Application system | Embedding clips | Emergency kit | 0-10V Dim. driver | DALI Driver | Sensor |
|--------------|-------------------|--------------------|-----------------|---------------|-------------------|-------------|--------|
| SW02 | Yes | Yes | | Yes | NA | NA | NA |

Similar products

| Orion |
|--|
|  3W |
| 7W |

| Mobility |
|--|
|  2W |
| |

| Kasiopeea |
|--|
|  2W |
| |

| Orion Clip |
|--|
|  3W |
| |