


Selene

10W 800 Lm / 830 Lm / 850 Lm

20W 1600 Lm / 1640 Lm / 1650 Lm

30W 2400 Lm / 2450 Lm / 2480 Lm

40W 3200 Lm / 3280 Lm / 3300 Lm



Scope of application

Commercial / Office / Conference Halls /
Advertising / Events / Fashion / Jewellery

Description

Selene is a luminaire with COB LED technology, adjustable on two axes, with high-efficiency metal reflection.

Simple and sleek look.

Lighting device made of unit cast aluminium alloy, with a good thermal dissipation effect.

Advantages

High luminous efficiency and energy saving.

Fitting

Fitting made of cast and finished aluminium alloy, frosted-white, grey or black powder coated.

Optics

Transparent and tempered PC or glass lens.

General Information

Mounting type: Suspended,
Surface-mounted, Flush-mounted

LED type: COB

Voltage: 100-277 VAC / 50 Hz

Operating temperature: -10 / +45

UGR: <19

CRI: >80

PF: >0.95

Angle: 12/24/40


Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm / W]	Colour Temp. ^[K]	Dimensions ^[mm]	Weight ^[kg]
SLN10WW-MW/S/BK	10	800	80	3000	172x114	0.8
SLN10NW-MW/S/BK	10	830	83	4000	172x114	0.8
SLN10W-MW/S/BK	10	850	85	6000	172x114	0.8
SLN20WW-MW/S/BK	20	1600	80	3000	177x135	1
SLN20NW-MW/S/BK	20	1640	83	4000	177x135	1
SLN20W-MW/S/BK	20	1650	85	6000	177x135	1
SLN30WW-MW/S/BK	30	2400	80	3000	180x144	1.2
SLN30NW-MW/S/BK	30	2450	82	4000	180x144	1.2
SLN30W-MW/S/BK	30	2480	83	6000	180x144	1.2
SLN40WW-MW/S/BK	40	3200	80	3000	181x169	1.4
SLN40NW-MW/S/BK	40	3280	82	4000	181x169	1.4
SLN40W-MW/S/BK	40	3300	83	6000	181x169	1.4

Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
ALL CODES					0-10	Yes	External

Photometric diagrams



Similar products

Kasa



18W	1500 Lm
30W	2250 Lm
35W	2620 Lm

Vero



18W	1500 Lm
30W	2250 Lm
35W	2620 Lm

Stil



30W	2150 Lm / 2400 Lm / 2650 Lm
------------	-----------------------------

Optional equipment

Filters

