

SLATE



Power^[W] / Luminosity^[Lm]

- 50 W > 6500 Lm
- 80 W > 10400 Lm
- 100 W > 13000 Lm
- 150 W > 19500 Lm
- 200 W > 26000 Lm



Description

- The Slate is a high-power industrial LED floodlight that offers an efficient alternative to traditional industrial lighting.
- Provides high-quality, controllable and highly efficient lighting.

General information

- Mounting type: On the end of a pole, applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -30 / +50
- UGR: <19
- CRI: >70
- PF: >0.9
- Angle: 110

Benefits

- Up to 80% less consumption than traditional appliances.
- Attractive, high-quality appearance.

Body & Optics

- Body made of pure die-cast and pressure-finished aluminium.
- Shock, moisture and dust resistant.
- Polycarbonate or glass lens dispenser, with clear lenses.

Applications

- Industrial, Commercial, Outdoor, Sports Lighting

SLATE

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
SLT50WW-S	50	6500	130	3000K	160x221x46	1.5
SLT50NW-S	50	6500	130	4000K	160x221x46	1.5
SLT50W-S	50	6500	130	6000K	160x221x46	1.5
SLT80WW-S	80	10400	130	3000K	231x264x53	2.3
SLT80NW-S	80	10400	130	4000K	231x264x53	2.3
SLT80W-S	80	10400	130	6000K	231x264x53	2.3
SLT100WW-S	100	13000	130	3000K	231x264x53	2.3
SLT100NW-S	100	13000	130	4000K	231x264x53	2.3
SLT100W-S	100	13000	130	6000K	231x264x53	2.3
SLT150WW-S	150	19500	130	3000K	240x325x57	3.3
SLT150NW-S	150	19500	130	4000K	240x325x57	3.3
SLT150W-S	150	19500	130	6000K	240x325x57	3.3
SLT200WW-S	200	26000	130	3000K	294x394x62	5.2
SLT200NW-S	200	26000	130	4000K	294x394x62	5.2
SLT200W-S	200	26000	130	6000K	294x394x62	5.2

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	External	Yes	Yes	NA