

SOEST COB



Power^[W] / Luminosity^[Lm]

- 13 W > 6600 Lm

General information

- Mounting type: Applied
- Type LED: COB
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 110

Applications

- Outdoor, Ornamental, Gardens and Parks Lighting

Description

- The Soest COB LED floodlight can perfectly replace traditional luminaires.
- It is an outdoor lighting fixture, applicable on walkways or walls made of high quality materials, finished to meet the highest customer demands.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; high stability of continuous operation.

Body & Optics

- Body in pure aluminium, cast and finished, electrostatically painted.
- PMMA disperser, matte milky-white, finely textured.

SOEST COB

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
SO13W-BK-COB	13	1300	100	6000K	200x56x152	1.5
SO13NW-BK-COB	13	1300	100	4000K	200x56x152	1.5
SO13WW-BK-COB	13	1300	100	3000K	200x56x152	1.5

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	Yes	NA	NA	NA	NA	External