

# STARKE

---



## Power<sup>[W]</sup> / Luminosity<sup>[Lm]</sup>

---

- 3.5 W > 270 Lm
- 7 W > 540 Lm



## General information

---

- Mounting type: Embedded
- Type LED: SMD
- Voltage: 100-240 VAC / 50-60Hz
- Operational temperature: -20 / +45
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 75

## Applications

---

- Outdoor, Commercial, Office and Residential Lighting

## Description

---

- Starke is an outdoor luminaire, recessed in exterior walls, made of high quality materials, finished to meet the highest customer demands.

## Benefits

---

- Modern and simple design
- Simple structure, easy to install.
- It saves energy compared to traditional appliances and is environmentally friendly.

## Body & Optics

---

- Aluminium alloy body, cast and finished, electrostatically painted, black.
- Transparent, tempered, PC disperser.



IP54 IK06

# STARKE

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm/W]</sup>	Colour temp. <sup>[K]</sup>	Measurements <sup>[mm]</sup>	Weight <sup>[kg]</sup>
STK07WW-BK	7	540	77	3000K	220x123x90	0.7
STK07NW-BK	7	540	77	4000K	220x123x90	0.7
STK07W-BK	7	540	77	6000K	220x123x90	0.7
STK035WW-BK	3.5	270	77	3000K	148x89x58	0.4
STK035NW-BK	3.5	270	77	4000K	148x89x58	0.4
STK035W-BK	3.5	270	77	6000K	148x89x58	0.4

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	Yes	NA	NA	NA	NA