

SVEN



Power^[W] / Luminosity^[Lm]

- 18 W > 990 Lm
- 24 W > 1320 Lm
- 36 W > 1980 Lm
- 48 W > 1440 Lm



General information

- Mounting type: Embedded
- Type LED: SMD
- Voltage: 24 VDC - 240 VAC
- Operational temperature: -20 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 15/25/45/60/Asymmetric

Applications

- Outdoor, Ornamental, Gardens and Parks Lighting

Description

- The Sven LED luminaire is a linear outdoor luminaire, recessed into outdoor floors, made of high quality, highly durable materials and finished to meet the highest customer demands.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

Body & Optics

- Body in pure aluminium, cast and finished, electrostatically painted.
- Transparent PMMA disperser

SVEN

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
SV18W-S	18	990	55	6000K	1050x75x84	2.8
SV18NW-S	18	990	55	4000K	1050x75x84	2.8
SV18WW-S	18	990	55	3000K	1050x75x84	2.8
SV24W-S	24	1320	55	6000K	1050x75x84	2.8
SV24NW-S	24	1320	55	4000K	1050x75x84	2.8
SV24WW-S	24	1320	55	3000K	1050x75x84	2.8
SV36W-S	36	1980	55	6000K	1050x75x84	2.8
SV36NW-S	36	1980	55	4000K	1050x75x84	2.8
SV36W-S	36	1980	55	3000K	1050x75x84	2.8
SV36RGB-S-24V	36	1080	30	RGB	1050x75x84	2.9
SV48RGB-S-24V	48	1440	30	RGB	1050x75x84	2.9

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	Yes	NA	Yes	Yes	NA