

T-LINE



Power^[W] / Luminosity^[Lm]

- 50 W > 8000 Lm



General information

- Mounting type: Applied
- Type LED: SMD
- Voltage: 200-240 VAC / 50-60Hz
- Operational temperature: -10 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 60/90

Applications

- Comercial, Horeca, Office Lighting

Description

- Energy efficient alternative.
- Low maintenance costs, better efficiency than traditional linear fluorescent fixtures.
- Can be used in a wide variety of industrial, commercial and office applications.
- The optimal solution for lighting systems due to low installation cost.

Benefits

- Easy to install: everything in a box, installation without additional tools.
- It reduces time and labour, packaging waste and complexity.
- Flexible solution, multiple angles possible.
- Possibility to integrate emergency kit, DALI pre-equipment or dimming.

Body & Optics

- White, black lamp body, modular, modern and simple design.
- Dispenser with multiple angle capability

T-LINE

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
TLINE5015W-WH/BK	50	8000	160	6000K	1493x60x11	
TLINE5015NW-WH/BK	50	8000	160	4000K	1493x60x11	
TLINE5015WW-WH/BK	50	8000	160	3000K	1493x60x11	

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	Yes	Yes	NA	Yes	Yes	Yes	Yes

Accessories



Suspension system



I connector



L connector



T connector



X connector



Cover



Supply



Rail