

THOR



Power^[W] / Luminosity^[Lm]

- 14 W > 770 Lm
- 15 W > 825 Lm
- 24 W > 1320 Lm
- 25 W > 1375 Lm



General information

- Mounting type: Embedded
- Type LED: SMD
- Voltage: 24 VDC - 240 VAC
- Operational temperature: -20 / +40
- UGR: <19
- CRI: >80
- PF: >0.9
- Angle: 15/25/45/60/Asymmetric

Applications

- Outdoor, Ornamental, Gardens and Parks Lighting

Description

- The Thor LED luminaire is an outdoor luminaire, recessed into outdoor floors, made of high quality, highly durable materials and finished to meet the highest customer demands.

Benefits

- Modern and simple design
- Simple structure, easy to install.
- Energy saving and environmentally friendly, CE RoHS compliant.
- High efficiency thermal management; low temperature operation; high stability of continuous operation.

Body & Optics

- Body in pure aluminium, cast and finished, electrostatically painted.
- Transparent PMMA disperser

THOR

Technical data

Code	Power ^[W]	Luminosity ^[Lm]	Efficiency ^[Lm/W]	Colour temp. ^[K]	Measurements ^[mm]	Weight ^[kg]
TH14W-S-24V	14	770	55	6000K	185x185x153	1.7
TH14NW-S-24V	14	770	55	4000K	185x185x153	1.7
TH14WW-S-24V	14	770	55	3000K	185x185x153	1.7
TH14RGB-S-24V	14	770	55	RGB	185x185x153	1.7
TH15W-S	15	825	55	6000K	185x185x153	1.7
TH15NW-S	15	825	55	4000K	185x185x153	1.7
TH15WW-S	15	825	55	3000K	185x185x153	1.7
TH15RGB-S	15	825	55	RGB	185x185x153	1.7
TH24W-S-24V	24	1320	55	6000K	215x215x173	1.9
TH24NW-S-24V	24	1320	55	4000K	215x215x173	1.9
TH24WW-S-24V	24	1320	55	3000K	215x215x173	1.9
TH24RGB-S-24V	24	1320	55	RGB	215x215x173	1.9
TH25W-S	25	1375	55	6000K	215x215x173	1.9
TH25NW-S	25	1375	55	4000K	215x215x173	1.9
TH25WW-S	25	1375	55	3000K	215x215x173	1.9
TH25RGB-S	25	1375	55	RGB	215x215x173	1.9

Code	System of suspension	Application system	Recessed clips	Kit of emergency	Driver size 0-10V	Driver DALI	Sensor
All codes	NA	NA	Yes	NA	Yes	Yes	NA