


# Vero

<b>10W</b>	730 Lm / 750 Lm / 760 Lm
<b>18W</b>	1400 Lm / 1430 Lm / 1450 Lm
<b>30W</b>	2430 Lm / 2470 Lm / 2490 Lm
<b>35W</b>	3040 Lm / 3070 Lm / 3090 Lm



## Scope of application

Commercial / Office / Conference Halls  
and Classrooms / Medical / Advertising

## Description

Vero is a luminaire with high-efficiency  
COB LED technology.

Simple and sleek look.

Lighting device made of unit cast  
aluminium alloy, with a good thermal  
dissipation effect.

High-temperature transparent resistant  
glass.

## Advantages

High luminous efficiency and energy saving.

## Fitting

Fitting made of cast and finished aluminium  
alloy, frosted-white, grey or black powder  
coated.

## Optics

Transparent and tempered PC or glass  
lens.

## General Information

**Mounting type:** Suspended, Surface-  
mounted, Flush-mounted

**LED type:** COB

**Voltage:** 110-277 VAC / 50 Hz

**Operating temperature:** -10 / +45

**UGR:** <19

**CRI:** >80

**PF:** >0.95

**Angle:** 12/24/40


## Technical data

Code	Power <sup>[W]</sup>	Luminosity <sup>[Lm]</sup>	Efficiency <sup>[Lm / W]</sup>	Colour Temp. <sup>[K]</sup>	Dimensions <sup>[mm]</sup>	Weight <sup>[kg]</sup>
VR10WW-MW/S/BK	10	730	73	3000	175x120x94	0.7
VR10NW-MW/S/BK	10	750	75	4000	175x120x94	0.7
VR10W-MW/S/BK	10	760	76	6000	175x120x94	0.7
VR18WW-MW/S/BK	18	1400	78	3000	145x206x166	0.8
VR18NW-MW/S/BK	18	1430	79	4000	145x206x166	0.8
VR18W-MW/S/BK	18	1450	81	6000	145x206x166	0.8
VR30WW-MW/S/BK	30	2430	81	3000	206x153x160	0.9
VR30NW-MW/S/BK	30	2470	82	4000	206x153x160	0.9
VR30W-MW/S/BK	30	2490	83	6000	206x153x160	0.9
VR35WW-MW/S/BK	35	3040	87	3000	198x198x125	1
VR35NW-MW/S/BK	35	3070	88	4000	198x198x125	1
VR35W-MW/S/BK	35	3090	89	6000	198x198x125	1

## Accessories

Product code	Suspension system	Application system	Embedding clips	Emergency kit	0-10V Dim. driver	DALI Driver	Sensor
ALL CODES					0-10	Yes	External

## Photometric diagrams



## Similar products

### Selene



<b>10W</b>	800 Lm / 830 Lm / 850 Lm
<b>20W</b>	1600 Lm / 1640 Lm / 1650 Lm
<b>30W</b>	2400 Lm / 2450 Lm / 2480 Lm
<b>40W</b>	3200 Lm / 3280 Lm / 3300 Lm

### Kasa



<b>18W</b>	1500 Lm
<b>30W</b>	2250 Lm
<b>35W</b>	2620 Lm

### Stil



<b>30W</b>	2150 Lm / 2400 Lm / 2650 Lm
------------	-----------------------------

## Optional equipment

### Filters

